

Legris D.O.T. Push-In Fittings

Features:

- materials: composite body, brass collet, stainless steel tube support, brass threads, Buna-N O-ring
- maximum operating pressure: **250 PSI** at ambient temperature
- temperature range: **-40°F to 200°F (-40°C to 93°C)**
- suitable fluids: compressed air only
- complies with the performance requirements of D.O.T FMVSS 571.106 (SAE J1131) and SAE J2494-3
- *These fittings are designed for use on all pneumatic circuits other than air brake assemblies between the frame and axle or between towed and towing vehicle.*



Male Connectors

Tube OD	Male NPT	Part #	Pkg Qty
5/32"	1/8"	31150411DOT	10
5/32"	1/4"	31150414DOT	10
3/16"	1/8"	31155511DOT	10
3/16"	1/4"	31155514DOT	10
1/4"	1/8"	31155611DOT	10
1/4"	1/4"	31155614DOT	10
1/4"	3/8"	31155618DOT	10
3/8"	1/8"	31156011DOT	10
3/8"	1/4"	31156014DOT	10
3/8"	3/8"	31156018DOT	10
3/8"	1/2"	31156022DOT	10
1/2"	1/4"	31156214DOT	10
1/2"	3/8"	31156218DOT	10
1/2"	1/2"	31156222DOT	10



- meets D.O.T. FMVSS571.106, SAE J2494 and SAE J2494-3

Female Connectors

Tube OD	Female NPT	Part #	Pkg Qty
5/32"	1/8"	31140411DOT	10
3/16"	1/8"	31145511DOT	10
1/4"	1/8"	31145611DOT	10
1/4"	1/4"	31145614DOT	10
3/8"	1/4"	31146014DOT	10
3/8"	3/8"	31146018DOT	10



- meets D.O.T. FMVSS571.106, SAE J2494 and SAE J2494-3