

## Type E Adapters with Swaged Ferrule

**Applications:**

- Developed specifically for chemical transport hoses having Crosslinked Polyethylene (XLPE) or Ultra High Molecular Weight Polyethylene (UHMW) tubes.

**Features:**

- provides a permanently attached cam and groove fitting when superior coupling retention is required
- testing tank transport hoses from a wide variety of manufacturers proved the swaged Boss-Lock™ fitting to be the leader in overall performance
- other sizes or hose OD's (available on special order), consult Dixon® for pricing and availability
- *special equipment required for installation*, consult Dixon® for pricing and availability or refer to page 85 for more information



Cam & Groove

Size	Hose OD		316 Stainless Steel Part #
	from	to	
¾"	1-6/64"	1-22/64"	<b>RE075-1370</b>
1"	1-29/64"	1-35/64"	<b>RE100-1620</b>
1"	1-36/64"	1-44/64"	<b>RE100-1770</b>

## Type E Adapters with Notched Shank adapter x hose shank


**Features:**

- can be removed from a damaged hose by cutting away the ferrule without necessarily damaging the fitting, *after inspection of the fitting to determine its suitability for reuse*, it can be reinstalled into another hose by using a *new ferrule*
- system allows you to better manage your inventory, stock one coupling and two ferrules and cover the same hose range with less inventory, *you must purchase a fitting and the matching ferrule to create an assembly*
- for use with notched ferrules below

Dixon® stems and ferrules are specifically designed to be used together as a coupling system. Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturer's stems or ferrules with Dixon® products.



swaged assembly



crimped assembly

Size	316 Stainless Steel Part #
1½"	<b>RE150NO</b>
2"	<b>RE200NO</b>
3"	<b>RE300NO</b>
4"	<b>RE400NO</b>

## Notched Ferrules

- reference notched shanks and adapters above
- Dixon® stems and ferrules are specifically designed to be used together as a coupling system. Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturer's stems or ferrules with Holedall™ products.



Size	Hose OD		304 Stainless Steel Part #
	From	To	
1½"	1-60/64"	2-12/64"	<b>GAS2334NO</b>
1½"	2-4/64"	2-22/64"	<b>GAS2370NO</b>
2"	2-30/64"	2-44/64"	<b>GAS2709NO</b>
2"	2-42/64"	2-54/64"	<b>GAS2885NO</b>
2½"	2-54/64"	3"	<b>GAS3012NO</b>
2½"	3-1/64"	3-13/64"	<b>GAS3260NO</b>
3"	3-30/64"	3-46/64"	<b>GAS3760NO</b>
3"	3-47/64"	3-54/64"	<b>GAS3885NO</b>
4"	4-40/64"	4-47/64"	<b>GAS5010NO</b>

