

Dixon PVC Flexible Suction Hose

Features:

- designed for drafting use only
- maximum operating pressure: **35 PSI**
- lightweight, flexible
- design incorporates engineered polymers and extruded aluminum parts to maximize strength, durability and performance.
- maximum operating pressure: **35 PSI**
- couplings - NST (NH), Cam and Groove, Storz, and special threads
- sizes - 2½", 3", 4", 4½", 5" and 6" standard smaller and larger diameters available, consult Dixon
- lengths - 10' standard length, other lengths available upon request, consult Dixon



female L/H x male R/L



storz x storz



cam & groove x cam & groove

Size	Length	Thread	Female L/H x Male Part #	Price/E	Female R/L x Male Part #	Price/E	Storz x Storz Part #	Price/E	Cam & Groove x Cam & Groove Part #	Price/E
2½"	10'	NST (NH)	FSH-9682-000	\$530.25	FSH-9682-050	\$530.25	FSH-9682-020	\$627.90	FSH-9682-030	\$690.90
		BAT	FSH-9682-000B	505.00	FSH-9682-050B	505.00	---	---	---	---
		CSA	FSH-9682-000C	505.00	FSH-9682-050C	505.00	---	---	---	---
		WCT	FSH-9682-000W	505.00	FSH-9682-050W	505.00	---	---	---	---
		NS1	FSH-9682-000NS	505.00	FSH-9682-050NS	505.00	---	---	---	---
		QST	FSH-9682-000Q	505.00	FSH-9682-050Q	505.00	---	---	---	---
3"	10'	NST (NH)	FSH-9682-100	744.45	FSH-9682-150	744.45	FSH-9682-120	828.45	FSH-9682-130	798.00
4"			FSH-9682-200	872.55	FSH-9682-250	872.55	FSH-9682-220	1170.75	FSH-9682-230	882.00
4½"			FSH-9682-300	1201.20	FSH-9682-350	1201.20	---	---	---	---
5"			FSH-9682-400	1275.75	FSH-9682-450	1275.75	FSH-9682-420	1530.90	FSH-9682-430	1328.25
6"			FSH-9682-500	1509.90	FSH-9682-550	1509.90	FSH-9682-520	2105.25	FSH-9682-530	1659.00

P